

The Superflat bathroom drain



Article information

Item no.: 42701.50 GTIN: 4026092028605

Price group: 10

Advantages

- Movable outlet socket
- Lip seal fixed on the drain body
- Side inlet via odour trap

Description

The Superflat bathroom drain is suitable for indoor floor drainage. The drain made of PP is equipped with a secure, reliably installed seal as well as a removable odour trap.

Variant

Waterproofing layer on the upper section: Enclosed sealing collar to be glued (bd) according to

DIN 18534

Sealing water height: 30 mm Discharge rate (l/s) with 20 mm backwater: 0,8

General characteristics

Nominal size (DN): 50 Outer diameter (OD): 50 mm

Dimensions

Vertical adjustment: 10 - 23 mm
Net weight: 1,35 kg
Gross weight: 1,59 kg
Cutout dimension, width: 180 mm
Cutout dimension, length: 260 mm

Vertical adjustment: vertically adjustable upper section

Length:312 mmWidth:312 mmPackaging dimension:lengthPackaging dimension:widthPackaging dimension:height

Tank/drain body

Number of outlets: 1

Inlet nominal size (DN): 40 mm Inlet type: 1



Material of drain body: PP

Coverage features

Type of cover: Slotted cover

Cover material: Stainless steel 14301

Colour of cover: silver
Width of cover: 95 mm
Length of cover: 95 mm

Surface: Polished SST

Frame material: Stainless steel 14301

Cover locking: placed

Load class: K 3 (EN 1253-1)

Rim length: 132 mm
Rim material: 132 mm
Shape of upper section: square
Upper section material: PP
Odour trap: included