

Shower channel Linearis Compact L: 850 mm, DN50, enclWPM, 304SSTcov, K3



Article information

Item no.: 45600.64 GTIN: 4026092046098

Price group: 10

Advantages

- Individual design with reversible stainless steel insert
- Low installation depth
- Highest fire protection standards

Description

The Linearis Compact shower channel with welded on drain body made of ABS is suitable for indoor linear drainage. If inserted upside down, the stainless steel insert can be tiled individually. Including prepared seepage water openings and odour trap.

Variant

System: 125 SonicControl: prepared

Waterproofing layer on the upper section: Enclosed sealing collar to be glued (bd) according to

DIN 18534

Water supply: W2-I
Sealing water height: 22 mm
Discharge rate (l/s) with 10 mm backwater: 0,6
Discharge rate (l/s) with 20 mm backwater: 0,7
Discharge rate (l/s) without backwater: 0,5 mm

General characteristics

Nominal size (DN): 50 Outer diameter (OD): 50 mm

Dimensions

Net weight: 2,23 kg Gross weight: 2,75 kgOuter dimension, length: 915 mm Installation depth: 80 - 140 mm Width: 191 mm Height: 80 mm Packaging dimension: width Packaging dimension: height Packaging dimension: length



Tank/drain body

Number of outlets: 1

Material of drain body: ABS

Coverage features

Type of cover: Stainless steel cover Cover material: Stainless steel 14301

Colour of cover: silver

Surface: Brushed SST

Frame material: Stainless steel 14301

Cover locking: placed

Load class: K 3 (EN 1253-1)
Grating colour: optionally tileable

Rim length: 66 mm
Rim material: 850 mm
Max. flooring height: 15 mm
Shape of upper section: square
Upper section material: ABS
Odour trap: included