

Parking deck drain, Ecoguss DN 125, square, Connection polymer pipe



Article information

Item no.: 48502 GTIN: 4026092036112 Price group: 40

Advantages

- Breakproof & load resistant
- withstand temperatures up to 400 degrees Celsius

Description

The Ecoguss parking deck drain is used for point drainage and is equipped with a sludge bucket. The recyclable composite material Ecoguss is temperature resistant and has a permanently corrosion-free surface. The outlet socket is suitable for connection to SML cast iron pipes. Separate equipotential bonding is not necessary. For products with pressure sealing flange: The pressure sealing flange with bolts and screws made of stainless steel is used for the clamping or welding of bitumen and polymer bitumen sheets as well as for polymer and elastomer sealing sheets. Only membranes tested by the manufacturer may be used for watertight seals. The outlet socket is suitable for connection to SML cast iron pipes. With connection option for equipotential bonding. It can be exposed to flames for short periods, 100 up to 400 degrees Celsius.

Variant System: Contents of sludge trap: Waterproofing layer on the drain body: Discharge rate (l/s) with 20 mm backwater:	125 yes Connection flange 4,5
General characteristics	
Standard:	EN 1253-2
Nominal size (DN):	125
Outer diameter (OD):	125 mm
Dimensions Net weight: Gross weight: Diameter: Cutout dimension, width: Cutout dimension, length: Width: Height:	2,86 kg 3,24 kg 290 mm 300 mm 300 mm 290 mm 196 mm



Length: Packaging dimension: Packaging dimension: Packaging dimension:

Tank/drain body Material of drain body: System:

Coverage features Type of cover: Cover material: Colour of cover: Width of cover: Length of cover: Surface: Frame material: Cover locking: Load class: Rim length: Rim material: Shape of upper section: Upper section material: Contents of sludge trap: 290 mm width height length

Ecoguss vertical

Round slotted cover Ecoguss black 234 mm 234 mm EDM Ecoguss Lock & Lift B 125 (EN 124) 247 mm 247 mm square Ecoguss yes