


Linearis Comfort upper section L: 750 mm, System 125, WaD, K 3



Article information

Item no.: 48928M
 GTIN: 4026092079041
 Price group: 10

Advantages

- Individual design with reversible stainless steel insert
- Highest fire protection standards
- Low installation depth

Description

Used in combination with a drain body of the KESSEL 125 modular system, the Linearis Comfort upper section is suitable for use as indoor linear drainage.

Variant

| | |
|--|--|
| System: | 125 |
| SonicControl: | open |
| Waterproofing layer on the upper section: | Factory-fitted sealing collar (WaD) according to DIN 18534 |
| Water supply: | W3-I |
| Sealing water height: | 50 mm |
| Discharge rate (l/s) with 10 mm backwater: | 1,1 |
| Discharge rate (l/s) without backwater: | 1 mm |

General characteristics

| | |
|----------------------|--------|
| Nominal size (DN): | 125 |
| Outer diameter (OD): | 125 mm |

Dimensions

| | |
|--------------------------|-------------|
| Net weight: | 3,44 kg |
| Gross weight: | 4,1 kg |
| Outer dimension, length: | 815 mm |
| Installation depth: | 80 - 140 mm |
| Width: | 243 mm |
| Height: | 110 mm |
| Packaging dimension: | width |
| Packaging dimension: | height |
| Packaging dimension: | length |

Coverage features

| | |
|----------------|-----------------------|
| Type of cover: | Stainless steel cover |
|----------------|-----------------------|

| | |
|-------------------------|-----------------------|
| Cover material: | Stainless steel 14301 |
| Colour of cover: | silver |
| Frame material: | Stainless steel 14301 |
| Cover locking: | placed |
| Load class: | K 3 (EN 1253-1) |
| Grating colour: | optionally tileable |
| Rim length: | 66 mm |
| Rim material: | 750 mm |
| Upper section material: | ABS |
| Odour trap: | included |