

Backwater valve Staufix DN 125, exposed, Type 1



Article information

Item no.: 720125
GTIN: 4026092076057
Price group: 10

Advantages

- Simple conversion to Staufix Type 2 or StaufixControl
- Flexible installation, various covers available for floor slab installation
- Simple, toolless maintenance and cleaning

Description

The backwater valve for wastewater without sewage is equipped with one mechanical flap which closes automatically in the event of backwater and also serves as an emergency closure to be closed by hand. Thanks to the modular KESSEL system, existing systems can easily be supplemented by a second flap or be converted to the StaufixControl backwater valve.

Variant

Emergency closure:	yes
Mechanical backwater flaps:	1

General characteristics

Colour:	black
Standard:	EN 13564
Nominal size (DN):	125
Outer diameter (OD):	125 mm
Type of wastewater:	without sewage
Installation situation:	exposed drainage pipe
Delivery state:	installation-ready
Backwater protection:	Type 1

Dimensions

Net weight:	3,1 kg
Gross weight:	5,7 kg
Vertical drop between inlet and outlet:	8 mm
Width:	216 mm
Height:	306 mm
Length:	511 mm
Packaging dimension:	width
Packaging dimension:	height

Packaging dimension:

length

Coverage features

Type of cover:

Lockable cover

Adjustment range:

One-handed closure