

Practicus basement drain DN 100, Black grating, Horizontal outlet



Article information

Item no.: 34101

GTIN: 4026092007884

Price group: 10

Advantages

- Vertically adjustable upper section
- Suitable for floor slab installation

Description

The Practicus basement drain is made of polymer and is suitable for floor slab installation. The upper section with slotted grating is vertically adjustable.

Variant

Contents of sludge trap: yes
Discharge rate (l/s) with 10 mm backwater: 1,1
Discharge rate (l/s) with 20 mm backwater: 1,8

General characteristics

Standard: EN 1253-2 Nominal size (DN): 100 Outer diameter (OD): 110 mm

Dimensions

Net weight: 1,39 kg
Gross weight: 1,61 kg
Cutout dimension, width: 180 mm
Cutout dimension, length: 220 mm
Installation depth: 152 - 208 mm

Vertical adjustment: vertically adjustable upper section

Length:

Northead adjustment:

Length:

Width:

Packaging dimension:

Packaging dimension:

Packaging dimension:

Width

Packaging dimension:

Packaging dimension:

Tank/drain body

Number of outlets:

Material of drain body: Polymer System: lateral

Coverage features



Type of cover: Slotted cover Cover material: Polymer Colour of cover: black Width of cover: 138 mm 138 mm Length of cover: Surface: Polished SST Frame material: Polymer Cover locking: placed

Load class: K 3 (EN 1253-1)

Shape of upper section: square
Upper section material: Polymer
Contents of sludge trap: yes
Odour trap: no