

Backwater valve Staufix Basic DN 125, Type 1 R, with emergency closure



Article information

Item no.: 72125R GTIN: 4026092028377 Price group: 10

Advantages

- Simple conversion possible using conversion kits
- Optional rat protection flap for additional safety
- Fast and toolless maintenance and cleaning

Description

The backwater valve for wastewater without sewage is equipped with one mechanical flap which closes automatically in the event of backwater and also serves as an emergency closure to be closed by hand. Thanks to the modular KESSEL system, existing systems can easily be supplemented by a second backwater flap.

Variant	
Stainless steel flap as rat protection:	yes
Emergency closure:	yes
Mechanical backwater flaps:	1
General characteristics Colour: Standard: Nominal size (DN): Outer diameter (OD): Type of wastewater: Installation situation: Delivery state: Backwater protection: purchasable by service partner:	black EN 13564 125 125 mm without sewage exposed drainage pipe installation-ready Type 1 No
	110
Dimensions	
Net weight:	2,1 kg
Gross weight:	2,1 kg
Vertical drop between inlet and outlet:	9 mm
Length:	405 mm
Width:	200 mm
Height:	280 mm



Packaging dimension: Packaging dimension: Packaging dimension:

Coverage features Adjustment range: length width height

Quick-release closure