

Backwater valve Staufix Basic OD 100, Type 1, with emergency closure



Article information

Item no.: 77100
GTIN: 4026092011294
Price group: 10

Advantages

- Simple conversion possible using conversion kits
- Optional rat protection flap for additional safety
- Fast and toolless maintenance and cleaning

Description

The backwater valve for wastewater without sewage is equipped with one mechanical flap which closes automatically in the event of backwater and also serves as an emergency closure to be closed by hand. Thanks to the modular KESSEL system, existing systems can easily be supplemented by a second backwater flap.

Variant

Stainless steel flap as rat protection:	no
Emergency closure:	yes
Mechanical backwater flaps:	1

General characteristics

Colour:	black
Standard:	EN 13564
Nominal size (DN):	100
Outer diameter (OD):	100 mm
Type of wastewater:	without sewage
Installation situation:	exposed drainage pipe
Delivery state:	installation-ready
Backwater protection:	Type 1
purchasable by service partner:	No

Dimensions

Net weight:	0,2 kg
Gross weight:	0,2 kg
Vertical drop between inlet and outlet:	9 mm
Length:	355 mm
Width:	155 mm
Height:	205 mm

Packaging dimension:
Packaging dimension:
Packaging dimension:

length
width
height

Coverage features
Adjustment range:

Quick-release closure