

## Grease separator EasyClean free NS 10, Direct, Insp. Wind., SonicControl



### Article information

Item no.: 93010.22/D  
GTIN: 4026092063668  
Price group: 60

### Advantages

- Direction of flow can be changed thanks to self-sealing interchangeable hubs (NS 2- NS 10)
- Low-maintenance operation
- Odour-reduced disposal with the tank closed

### Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. A direct disposal pipe socket is available for odour-reduced manual disposal. After disposal, a maximum of 3 litres residual sludge volume is left in the tank. 20 year polyethylene warranty.

#### Variant

|   |                     |
|---|---------------------|
| Disposal variant:                         | Direct              |
| Protection class motor:                   | no                  |
| Sludge bucket:                            | yes                 |
| Nominal size (NS):                        | 10                  |
| SonicControl:                             | yes                 |
| Disposal system:                          | Disposal connection |
| Refill inlet in accordance with DIN 1988: | no                  |
| Type of disposal:                         | manual              |
| Load-bearing capacity (DIN 19901):        | F3                  |

#### General characteristics

|                                 |   |
|---------------------------------|---|
| Material:                       | PE  |
| Standard:                       | EN 1825   |
| Installation situation:         | free-standing installation                                      |
| Delivery state:                 | Installation-ready (connection parts must be connected on site) |
| Scope of delivery:              | Storz-B coupling R 2 1/2" for disposal vehicle connection       |
| purchasable by service partner: | No  |

**Dimensions**

|                               |         |
|-------------------------------|---------|
| Net weight:                   | 199 kg  |
| Gross weight:                 | 242 kg  |
| Set-up area, length:          | 2822 mm |
| Set-up area, width:           | 973 mm  |
| Set-up area, height:          | 1653 mm |
| Required access area, length: | 2590 mm |
| Required access area, width:  | 940 mm  |
| Required access area, height: | 1653 mm |
| Packaging dimension:          | length  |
| Packaging dimension:          | width   |
| Packaging dimension:          | height  |

**Tank/drain body**

|   |   |
|---|---|
| Nominal pressure (PN):                      | 10  |
| Pressure pipe connection (DN):              | 65  |
| Pressure pipe connection (OD):              | 75 mm   |
| Distance pipe bottom outlet to tank bottom: | 1185 mm   |
| Distance pipe bottom inlet to tank bottom:  | 1255 mm   |
| Outlet nominal size (OD):                   | 160 mm  |
| Outlet nominal size (DN):                   | 150 mm  |
| Inlet nominal size (DN):                    | 160 mm  |
| Inlet nominal size (DN):                    | 150 mm  |
| Connection inlet/outlet sockets:            | PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS |
| Servicing opening:                          | 420 mm  |

**Coverage features**

|                  |                       |
|------------------|-----------------------|
| Type of cover:   | Cover                 |
| Cover material:  | Polymer               |
| Colour of cover: | violet                |
| Cover locking:   | Quick-release closure |
| Tightness:       | odour-tight           |

**Wastewater contents**

|                                   |        |
|-----------------------------------|--------|
| Separator contents:               | 900 l  |
| Total volume:                     | 1900 l |
| Hose:                             | 1000 l |
| Storage quantity of light liquid: | 400 l  |

**Control**

|                  |       |
|------------------|-------|
| Control unit:    | no    |
| Mains frequency: | 50 Hz |