

## Backwater valve *Staufix FKA*

Installation in a concrete slab / floor




TÜV Rheinland Germany type tested and monitored

**CE** EN 13564 Type 3 F

Made of polymer, with telescopic upper section for continuous height- and level adjustment. For installation depth (D) from 486 – 640 mm, Installation area 750 × 750 mm With surface water tight cover plate class A 15 made of polymer. Installation kit with choice of cover. Backwater valve according to EN 13564 Type 3 with two open flaps. Plug-and-Play control unit with connection option to building management system and alarm, protection type IP 54, with integrated self diagnosis system SDS, display for operating status and battery back-up, motor is rated protection Type IP 68 (3 m, 24 h). Supply voltage/-frequency: 230 V AC/50 Hz. **Power cable length:** 5 m (15 m available on request).

**Accessories:**

- Extension sections for installation in waterproof concrete see page 52
- Conversion kits see page 35



**Outer diameter Ø (mm)**      **L × H in mm**      **Art. no.**

With recessed cover for on-site tiling

Ø 110	642 × 394	<b>84 100X</b>
Ø 125	645 × 387	<b>84 125X</b>
Ø 160	656 × 370	<b>84 150X</b>
Ø 200*	720 × 348	<b>84 200X</b>

With black cover

Ø 110	642 × 394	<b>84 100S</b>
Ø 125	645 × 387	<b>84 125S</b>
Ø 160	656 × 370	<b>84 150S</b>
Ø 200*	720 × 348	<b>84 200S</b>

\* In-/Outlet Ø 200, hydraulics corresponds to Ø 160

## Backwater valve *Staufix FKA*

Installation in an exposed wastewater pipe




TÜV Rheinland Germany type tested and monitored

**CE** EN 13564 Type 3 F

Made of polymer, with protective cover. Backwater valve according to EN 13564 Type 3 with two open flaps. Plug-and-Play control unit with connection option to building management system and alarm, display for operating status and battery back-up, protection type IP 54, with integrated self diagnosis system SDS, display for operating status and battery back-up, motor is rated protection Type IP 68 (3 m, 24 h). Supply voltage/-frequency: 230 V AC/50 Hz. **Power cable length:** 5 m (15 m available on request).

**Accessories:**

- Conversion kits see page 35



**Outer diameter Ø (mm)**      **L × H in mm**      **Art. no.**

Ø 110	642 × 422	<b>84 100</b>
Ø 125	645 × 422	<b>84 125</b>
Ø 160	656 × 422	<b>84 150</b>
Ø 200*	720 × 422	<b>84 200</b>

\* In-/Outlet Ø 200, hydraulics corresponds to Ø 160