


Clean out *Controlfix*

Installation in an exposed wastewater pipe



Made of polymer, with protective cover.

➤ **Accessories:**  
Conversion kits see below



| Outer diameter<br>Ø (mm) | L × H in mm | Art. no. |
|--------------------------|-------------|----------|
| Ø 110                    | 642 × 422   | 80 100   |
| Ø 125                    | 645 × 422   | 80 125   |
| Ø 160                    | 656 × 422   | 80 150   |
| Ø 200*                   | 720 × 422   | 80 200   |

\* In-/Outlet Ø 200, hydraulics corresponds to Ø 160

Conversion kits

for *Pumpfix F*, *Staufix FKA* and *Staufix SWA* models made on or after Jan 2011

|  |  |  | Art. no. |
|--|--|--|----------|
| <b>Backwater pumping</b><br><i>Pumpfix F</i><br>for installation in a concrete slab/floor      | <b>Compatibility:</b> For Ø 110 – Ø 200*<br><b>Inclusive:</b> Comfort control unit with recessed cover for on-site tiling and drain, <i>Multistop</i> , gasket<br><b>Cable length:</b> 5 m<br>➤ <b>Cable extension:</b> See page 52  |  | 80 098   |
| <b>Backwater pumping</b><br><i>Pumpfix F</i><br>for installation in an exposed wastewater pipe | <b>Compatibility:</b> For Ø 110 – Ø 200*<br><b>Inclusive:</b> Comfort control unit<br><b>Cable length:</b> 5 m<br>➤ <b>Cable extension:</b> See page 52  |  | 80 097   |
| <b>Motorized backwater valve</b><br><i>Staufix FKA</i>   | <b>Compatibility:</b> For installation in a concrete slab/floor and in an exposed wastewater pipe, for Ø 110 – Ø 200*<br><b>Inclusive:</b> Comfort control unit<br><b>Cable length:</b> 5 m<br>➤ <b>Cable extension:</b> See page 52 |  | 80 093   |
| <b>Backwater valve</b><br><i>Staufix SWA</i>   | <b>Compatibility:</b> For installation in a concrete slab/floor and in an exposed wastewater pipe, for Ø 110 – Ø 200*<br><br>* In-/Outlet Ø 200, hydraulics corresponds to Ø 160   |  | 80 091   |