


Twin flap backwater valve *StaufixControl*

Installation in a concrete slab / floor



TÜV Rheinland Germany type tested and monitored  EN 13564 Type 2

Made of polymer, with telescopic upper section for continuous height- and level adjustment.

For installation depth (D)

Ø 90 – 110, 276 – 399 mm

Ø 125 – 200, 328 – 450 mm,


Installation area 750 × 750 mm


With surface water tight cover plate class A 15 made of polymer.

Installation kit with choice of cover.

Backwater valve according to EN 13564 Type 2 with two self-closing flaps, one of which can be locked by hand as an emergency closure.

Warning: With visual and acoustic warning in the event of backwater.



 **Accessories:** see page 52 – 55

Without rodent protection (two polymer flaps)

Outer diameter Ø (mm)	L × H in mm	Art. no.
--------------------------	-------------	----------

With recessed cover for on-site tiling

Ø 90	389 × 179	770 090.10X
Ø 110	389 × 179	770 100.10X
Ø 125	515 × 222	770 125.10X
Ø 160	526 × 205	770 150.10X
Ø 200*	590 × 185	770 200.10X

With black cover

Ø 90	389 × 179	770 090.10S
Ø 110	389 × 179	770 100.10S
Ø 125	515 × 222	770 125.10S
Ø 160	526 × 205	770 150.10S
Ø 200*	590 × 185	770 200.10S

With rodent protection (one polymer and one stainless steel flap)

Outer diameter Ø (mm)	L × H in mm	Art. no.
--------------------------	-------------	----------

With recessed cover for on-site tiling

Ø 90	389 × 179	770 090.10XR
Ø 110	389 × 179	770 100.10XR
Ø 125	515 × 222	770 125.10XR
Ø 160	526 × 205	770 150.10XR
Ø 200*	590 × 185	770 200.10XR

With black cover

Ø 90	389 × 179	770 090.10SR
Ø 110	389 × 179	770 100.10SR
Ø 125	515 × 222	770 125.10SR
Ø 160	526 × 205	770 150.10SR
Ø 200*	590 × 185	770 200.10SR