

Twin flap backwater valve *Staufix*

Installation in a concrete slab / floor



TÜV Rheinland Germany type tested and monitored

EN 13564 Type 2

Made of polymer, with telescopic upper section for continuous height- and level adjustment.

For installation depth (D)

Ø 90 – 110, 276 – 399 mm

Ø 125 – 200, 328 – 450 mm,

Installation area 750 × 750 mm


With surface water tight cover plate class A 15 made of polymer.

Installation kit with choice of cover.

Backwater valve according to EN 13564 Type 2 with two self-closing flaps, one of which can be locked by hand as an emergency closure.

Note: Can be retrofitted on the *StaufixControl*.

Accessories: see page 52 – 55



Without rodent protection (two polymer flaps)

Outer diameter Ø (mm)	L × H in mm	Art. no.
--------------------------	-------------	----------

With recessed cover for on-site tiling

Ø 90	389 × 179	730 090.10X
Ø 110	389 × 179	730 100.10X
Ø 125	515 × 222	730 125.10X
Ø 160	526 × 205	730 150.10X
Ø 200*	590 × 185	730 200.10X

With black cover

Ø 90	389 × 179	730 090.10S
Ø 110	389 × 179	730 100.10S
Ø 125	515 × 222	730 125.10S
Ø 160	526 × 205	730 150.10S
Ø 200*	590 × 185	730 200.10S

With rodent protection (one polymer and one stainless steel flap)

Outer diameter Ø (mm)	L × H in mm	Art. no.
--------------------------	-------------	----------

With recessed cover for on-site tiling

Ø 90	389 × 179	730 090.10XR
Ø 110	389 × 179	730 100.10XR
Ø 125	515 × 222	730 125.10XR
Ø 160	526 × 205	730 150.10XR
Ø 200*	590 × 185	730 200.10XR

With black cover

Ø 90	389 × 179	730 090.10SR
Ø 110	389 × 179	730 100.10SR
Ø 125	515 × 222	730 125.10SR
Ø 160	526 × 205	730 150.10SR
Ø 200*	590 × 185	730 200.10SR

* In-/Outlet Ø 200, hydraulics corresponds to Ø 160