

Twin flap backwater valve *Staufix*

Installation in an exposed wastewater pipe

TÜV Rheinland Germany type tested and monitored  EN 13564 Type 2

Made of polymer. Backwater valve according to EN 13564 Type 2 with two self-closing flaps, one of which can be locked by hand as an emergency closure.

Note: Can be retrofitted on the *StaufixControl*.

 **Accessories:** see page 52 – 55




Without rodent protection
(two polymer flaps)

Outer diameter Ø (mm)	L × H in mm	A × B in mm	Art. no.
Ø 90	386 × 230	193 × 167	730 090
Ø 110	389 × 230	193 × 167	730 100
Ø 125	515 × 306	263 × 214	730 125
Ø 160	526 × 306	263 × 214	730 150
Ø 200*	590 × 306	263 × 214	730 200

With rodent protection
(one polymer and one stainless steel flap)

Outer diameter Ø (mm)	L × H in mm	A × B in mm	Art. no.
Ø 90	386 × 230	193 × 167	730 090R
Ø 110	389 × 230	193 × 167	730 100R
Ø 125	515 × 306	263 × 214	730 125R
Ø 160	526 × 306	263 × 214	730 150R
Ø 200*	590 × 306	263 × 214	730 200R



* In-/Outlet Ø 200, hydraulics corresponds to Ø 160