

Single flap backwater valve *Staufix*

Installation in a concrete slab / floor



TÜV Rheinland Germany type tested and monitored

EN 13564 Type 1

Made of polymer, with telescopic upper section for continuous height- and level adjustment.

For installation depth (D)

Ø 90 – 110, 276 – 399 mm

Ø 125 – 200, 328 – 450 mm,

Installation area 750 × 750 mm

With surface water tight cover plate class A 15 made of polymer.

Installation kit with choice of cover.

Backwater valve according to EN 13564 Type 1

with one self-closing flap, can be locked by hand as an emergency closure.

Note: Can be upgraded to *Staufix* Type 2.

➤ **Accessories:** see page 52 – 55



Outer diameter
Ø (mm)

L × H in mm


Art. no.

With recessed cover for on-site tiling

Ø 90	389 × 179	720 090.10X
Ø 110	389 × 179	720 100.10X
Ø 125	515 × 222	720 125.10X
Ø 160	526 × 205	720 150.10X
Ø 200*	590 × 185	720 200.10X

With black cover

Ø 90	389 × 179	720 090.10S
Ø 110	389 × 179	720 100.10S
Ø 125	515 × 222	720 125.10S
Ø 160	526 × 205	720 150.10S
Ø 200*	590 × 185	720 200.10S



* In-/Outlet Ø 200, hydraulics corresponds to Ø 160

Single flap backwater valve *Staufix*

Installation in an exposed wastewater pipe



TÜV Rheinland Germany type tested and monitored

EN 13564 Type 1

Made of polymer

Backwater valve according to EN 13564 Type 1

with one self-closing flap, can be locked by hand as an emergency closure.

Note: Can be upgraded to *Staufix* Type 2.

➤ **Accessories:** see page 52 – 55




Outer diameter
Ø (mm)

L × H in mm

A × B in mm

Art. no.

Ø 90	386 × 230	193 × 167	720 090
Ø 110	389 × 230	193 × 167	720 100
Ø 125	515 × 306	263 × 214	720 125
Ø 160	526 × 306	263 × 214	720 150
Ø 200*	590 × 306	263 × 214	720 200



* In-/Outlet Ø 200, hydraulics corresponds to Ø 160