


Twin flap backwater valve *Staufix Basic*

Installation in an exposed wastewater pipe



CE EN 13564 Type 2

Made of polymer.
 Installation area 650 × 300 mm
 Twin flaps, self-closing, one of which can be locked by hand as an emergency closure.
 Inlet/outlet for connection to PVC pipe according to EN 1566-1.



Without rodent protection (two polymer flaps)

Outer diameter Ø (mm)	L × H in mm	A × B in mm	Art. no.
Ø 110	355 × 180+25	205 × 155	73 100
Ø 125	405 × 240+40	270 × 200	73 125
Ø 160	450 × 240+40	270 × 200	73 150
Ø 200	530 × 278+50	353 × 248	73 200

With rodent protection (one polymer and one stainless steel flap)

Outer diameter Ø (mm)	L × H in mm	A × B in mm	Art. no.
Ø 110	355 × 180+25	205 × 155	73 100R
Ø 125	405 × 240+40	270 × 200	73 125R
Ø 160	450 × 240+40	270 × 200	73 150R


Single flap backwater valve *Staufix Basic*

Installation in an exposed wastewater pipe



CE EN 13564 Type 1

Made of polymer
 Installation area 650 × 300 mm
 Self-closing flap, can be locked by hand as an emergency closure.
 Inlet/outlet for connection to PVC pipe according to EN 1566-1.



Without rodent protection (one polymer flap)

Outer diameter Ø (mm)	L × H in mm	A × B in mm	Art. no.
Ø 100	355 × 180+25	205 × 155	77 100
Ø 110	355 × 180+25	205 × 155	72 100
Ø 125	405 × 240+40	270 × 200	72 125
Ø 160	450 × 240+40	270 × 200	72 150
Ø 200	530 × 278+50	353 × 248	72 200

With rodent protection (one stainless steel flap)

Outer diameter Ø (mm)	L × H in mm	A × B in mm	Art. no.
Ø 110	355 × 180+25	205 × 155	72 100R
Ø 125	405 × 240+40	270 × 200	72 125R
Ø 160	450 × 240+40	270 × 200	72 150R


Single flap backwater valve *Staufix Basic*

Installation in an exposed wastewater pipe



CE EN 13564 Type 0

Made of polymer
 Installation area 650 × 300 mm
 Self-closing flap.
 Inlet/outlet for connection to PVC pipe according to EN 1566-1.



Outer diameter Ø (mm)	L × H in mm	A × B in mm	Art. no.
Ø 100	355 × 170	205 × 155	76 100
Ø 110	355 × 170	205 × 155	71 100
Ø 125	405 × 230	270 × 200	71 125
Ø 160	450 × 230	270 × 200	71 150
Ø 200	530 × 278	353 × 248	71 200

- Conversion kits: page 46
- Accessories: pages 52 – 55