

## Clean out *Staufix Basic*

Installation in an exposed wastewater pipe




Made of polymer.

Installation area 650×300 mm

Upgradable to all *Staufix* model backwater valves




- **Conversion kits:** see below
- **Accessories:** pages 52 – 55



Outer diameter Ø (mm)	L × H in mm	A × B in mm	Art. no.
Ø 110	355 × 170	205 × 155	<b>70 100</b>
Ø 125	405 × 230	270 × 200	<b>70 125</b>
Ø 160	450 × 230	270 × 200	<b>70 150</b>
Ø 200	530 × 278	353 × 248	<b>70 200</b>

## Conversion kits

for *Staufix Basic* from 04/2005 to 12/2017

			Outer diameter Ø (mm)	Art. no.	
<b>for upgrade to Type 2</b> (Twin flap backwater valve <i>Staufix</i> )	<b>Function:</b> The <i>Staufix Basic</i> clean out body can be converted to a <b><i>Staufix Basic</i> twin flap backwater valve</b> by means of two backwater flaps, the insert flap housing and the lockable cover.	<b>Backwater flap</b>		Ø 110	<b>70 231</b>
				Ø 125	<b>70 232</b>
				Ø 160	<b>70 232</b>
				Ø 200	<b>70 205</b>
				<b>Insert flap housing</b>	
Ø 125	<b>70 242</b>				
Ø 160	<b>70 242</b>				
Ø 200	<b>70 205</b>				
<b>for upgrade to Type 1</b> (Single flap backwater valve <i>Staufix</i> )	<b>Function:</b> The <i>Staufix Basic</i> clean out body can be converted to a <b><i>Staufix Basic</i> single flap backwater valve with emergency closure</b> by means of the backwater flap, insert flap housing and the lockable cover.	<b>Lockable cover incl. emergency closure and sealing gasket</b>		Ø 110	<b>70 261</b>
				Ø 125	<b>70 262</b>
				Ø 160	<b>70 262</b>
				Ø 200	<b>70 203</b>
<b>for upgrade to Type 0</b> (Single flap backwater valve <i>Staufix</i> )	<b>Function:</b> The <i>Staufix Basic</i> clean out body can be converted to a <b><i>Staufix Basic</i> single flap backwater valve</b> by means of a backwater flap (for <i>Staufix Basic</i> from 04/2005).				