Accessories

Pumpfix F, Staufix FKA, Staufix SWA and Controlfix

Hygiene and odo	ur stop			Cover	Art. no
Drain body	Compatibility: For lowest installation; for backwater pumping station <i>Pumpfix F</i>	7		black grey	680 79 680 79
Drain body	Compatibility: Seal water height 50 mm; for backwater pumping station <i>Pumpfix F</i>	9		black grey	680 79 680 79
additionally <i>Multistop</i>	Compatibility: For backwater pumping station <i>Pumpfix F</i> Function: Odour, foam, rodent and insect stop	Ģ			48 500
additionally <i>Megastop</i>	Compatibility: For backwater pumping station <i>Pumpfix F</i> Function: Mechanical odour trap inclusive hair filter for KESSEL upper sections	9	^{Ø121} , *		48 550
additionally odour trap	Compatibility: For backwater pumping station <i>Pumpfix F</i> Seal water height: 50 mm (Ventilation always required when in use!)	T			680 696
Hygiene					Art. no
Hair filter	Compatibility: Art. no. 48 500; for lifting station <i>Aqualift F Compact</i> , <i>Aqualift S Compact</i> and <i>Minilift S</i> (280 570X, 280 570S, 280 570XC and 280 570SC)				48 700
Rodent / Insect for Staufix FKA and S					Art. no
Rat protection flap	Compatibility: <i>Staufix FKA</i> from 01/2011 to 2015 (with flap in pendulum position) Inclusive: Stainless steel shield	Û			80 03
Maintenance					Art. no
Testing funnel	Compatibility: For all <i>Staufix FKA</i> and <i>Staufix SWA</i> backwater valves (Ø 110, Ø 125, Ø 160) Inclusive: Gasket	9	R 1/2		70 214