Accessories

Pumpfix F, Staufix, Staufix FKA, Staufix SWA and Controlfix

Control unit acco	essories			Art. no.
Audible alarm	Compatibility: For all control units with SDS function Cable length: 20 m	à		20 162
Potential-free contact	Compatibility: For all control units up to 12/2016 with SDS function	a start		80 072
Activation code for potential-free contact	Compatibility: For Comfort control units beginning model year 2017			80 077
Radio receiver				Art. no.
Radio-based audible alarm	Compatibility: For backwater valve <i>StaufixControl</i> Function: For forwarding a visual and acoustic signal in the event of backwater	•		72 222
Wireless ,kill' plug	Compatibility: For backwater valve <i>StaufixControl</i> Function: For killing power in the event of backwater (e.g. washing machine)			72 223
Conversion kits			Outer diameter Ø (mm)	Art. no.
Rodent protection flap	Compatibility: Art. no. 70 100, 70 125, 70 150, 71 100, 71 125, 71 150 72 100, 72 125, 72 150, 73 100, 73 125, 73 150, 720, 730, 770 Material: Made of stainless steel	Ò	Ø 90 - Ø 110 Ø 125 - Ø 200	70 233 70 234
Backwater flap	Compatibility: For upgrade from type 1 to type 2	Ì	Ø 90 - Ø 110 Ø 125 - Ø 200	70 231 70 232