-−Ø 330

for installation in waterproof concrete

Elastomer waterproofing membrane

Accessories

Staufix and StaufixControl

Extension sections

made of polymer



with flange for deeper installation

Inclusive: Sealing Extension: Max. 147 mm Note: In case of deeper installation ensure maintenance capability!

Art. no. 830 070

Lockable cover




Lockable cover Control

Compatibility:

- for Type 1 and Type 2
- Conversion kit as an upgrade to *StaufixControl*

Warning: With visual and acoustic warning in the event of backwater.

Ø 90 - Ø 110	Art. no. 72 224
Ø 125 - Ø 200	Art. no. 72 225



with flange and counter flange for deeper installation	
Material: Counter flange	
made of stainless steel	
Inclusive: Sealing	
Extension: Max. 147 mm	
Compatibility: For connection	
to an on-site membrane	
Note: In case of deeper installation	
ensure maintenance capability!	

Art. no. 830 073

Spigot / Socket made of polymer



Spigot

removable fitting mountable on both sides and in different dimensions

Ø 90	Art. no. 83 090
Ø 100	Art. no. 830 200
Ø 110	Art. no. 830 100
Ø 125	Art. no. 83 082
Ø 160	Art. no 83 083
Ø 200	Art. no. 83 084



Socket

with flange

Art. no. 830 075

Inclusive sealing set:

made of NK/SBR Ø 700 mm

Note: Suitable for installation in the concrete slab/floor.

Extension: Max. 294 mm Delivery: Completely assembled.

removable fitting mountable on both sides and in different dimensions

Ø 90	Art. no. 83 091
Ø 100	Art. no. 830 202
Ø 110	Art. no. 830 101
Ø 125	Art. no. 83 086
Ø 160	Art. no. 83 087
Ø 200	Art. no. 83 088