

# Lifting station *Aqualift F Compact Mono / Duo*

for installation in a concrete slab / floor



Z-53.2-484 Max 2 WC connections

Tank volume: 40 liters  
Pump volume: 20 liters

**Polyethylene storage chamber** for installation in a concrete slab / floor, with recessed cover for on-site tiling and drain, installation depth (D) 490 to 600 mm, with odour trap, sealing water height 50 mm, with lateral inlet Ø 110.

Installation area 800 × 800 mm.

### Upper section and cover

With telescopic upper section for free height and level adjustment, recessed cover for on-site tiling, made of polymer class A 15, with moisture protective sealing flange.

### Pump

Single or twin removable SPZ pump(s) with macerator, pressure sensor controlled, with integrated backwater flap.

### Control unit

with SDS control unit (self-diagnosis system) for fully automatic pump control, splash water protected (IP 54), wall mounted.

Pressure connection: 1 1/2 inch outer thread or pressure pipe Ø 40 mm for PVC glued connection or pressure pipe set (Art. no. 28 040).

Power cable length: 5 m

**Note:** A ventilation pipe must be provided for on site.

➤ **Accessories:** page 127 – 133



Illustration shows Mono version 28 701X






Illustration shows Duo version 28 704X



### Pumping capacity



### Pump type

Pump type	Current type	Voltage	Current	Power P1/P2	RPM	Motor protection	Pumping height	Pumping capacity
SPZ 1000-S3-30%*	Alternating current	230 V	5.2 A	1.2 kW / 0.69 kW	2800 min <sup>-1</sup>	integrated	10 m	11.5 m³/h
SPZ 1000-S3-30% resistant*	Alternating current	230 V	5.2 A	1.2 kW / 0.69 kW	2800 min <sup>-1</sup>	integrated	10 m	11.5 m³/h

\*Definition of S3-pumps see page 97

### Mono version with one pump

SPZ pump	Voltage	Art. no.
<b>With recessed cover for on-site tiling</b>		
1000-S3	230 V	<b>28 701X</b>
1000-S3 resistant	230 V	<b>28 701XC</b>
<b>With black cover</b>		
1000-S3	230 V	<b>28 701S</b>
1000-S3 resistant	230 V	<b>28 701SC</b>

### Duo version with two pumps

SPZ pump	Voltage	Art. no.
<b>With recessed cover for on-site tiling</b>		
1000-S3	230 V	<b>28 704X</b>
1000-S3 resistant	230 V	<b>28 704XC</b>
<b>With black cover</b>		
1000-S3	230 V	<b>28 704S</b>
1000-S3 resistant	230 V	<b>28 704SC</b>