

Lifting station *Aqualift S 100 / S 200*



The flexible option for free-standing set-up.

Flexible and powerful: The *Aqualift S 100 / S 200* lifting station is the perfect choice for renovation or other installation situations that require free-standing set-up. Due to its small installation area, it can also be easily integrated in small rooms by retrofitting. And thanks to the one-handed closure that can be operated without tools, maintenance is quick and easy.



1 Lifting station 2 Grease separator 3 Pressure pipe

Wastewater tank

Tanks with 100 and 200 l capacity are available to choose from. Both tanks fit through standard size doors with 80 cm wide passage. They can therefore be retrofitted into most rooms without any issue.

Pumps

The *Aqualift S 100 / S 200* is equipped with one or two pumps. There are two models to choose from: a 650 watt pump with S1 mode (continuous operation) with float switch or control unit and a 1.3 kilowatt pump with S3 mode (non-continuous operation) with control unit. Both pump types handle faecal-free wastewater by means of a multi-vane impeller.

Ideal for connecting to grease separators

The *Aqualift S 100 / S 200 Duo* with two pumps is ideally suited for drainage systems which cannot afford to go off-line – for example directly after a grease separator.

The large easy-access maintenance cover, which can be opened in seconds using the tool free one-handed closure, also contributes to the system's ease of use. An additional advantage is the norm approved integrated sampling chamber located inside the *Aqualift S*. With the new *Aqualift S 100 / S 200*, an extra sampling chambers is no longer required.