## Lifting station Aqualift S 100 Mono

for free-standing installation and wastewater without sewage

#### EN 12050-2

**Lifting station** for faecal-free wastewater, free-standing set-up, preassembled for final installation on site.

- With odour-tight cover and quick-release closure for easy maintenance
- Tank made of PE, resistant to aggressive wastewater
- Including backflow preventer for the pressure pipe
- Including socket Ø 110 mm for inlet and sampling
- Pump/s with multi-vane impeller for maximum operating reliability

#### Version:

Type of system: Single station / Pump control: Float switch / Backflow preventer: integrated / Installation situation: free-standing set-up / Type of wastewater: wastewater without sewage General characteristics:

Colour: black / Standard: EN 12050-2

**Dimensions:** 

Length: 670 mm / Width: 530 mm / Height: 650 mm

Tank:

Inlet nominal size ( $\emptyset$ ): 110 mm / Tank volume: 120 l /

Pressure pipe connection (Ø): 63 mm

Pumping volume: 25 l Coverage features:

Cover material: Polymer / Colour of cover: violet / Tightness: odour-tight / Locking: Quick-release closure

Free passage: 10 mm

Pump:

Type of fuse required (electrical protection): C 16 A / Max. temperature (permanent) of conveyed material: 40 °C / Connection type: Schuko (earthed contact) 2-pin / Length of mains cable for pump: 5 m / Protection class (pump): IP 68 (3 m) / Type of pump connection cable: H07RN-F 3G 1.0 mm² Note: Pumps available as resistant versions on request: individual@kessel.de


→ Accessories: page 127 – 133





Illustration shows Art. no. 28 511

# 







Illustration shows: Art. no. 28 511

### **Pumping capacity**



Pump type	Voltage	Current	Power (P1/P2)	RPM	Pumping height	Pumping capacity
GTF 600-S1*	200 . 002	2.9 A	0.65 kW / 0.4 kW	2750 min <sup>-1</sup>	8 m	12 m³/h
GTF 1250-S3*		5.4 A	1.3 kW / 0.8 kW	2700 min <sup>-1</sup>	11 m	20 m³/h

<sup>\*</sup>Definition of S1 and S3-pumps see page 97















GTF pump	Voltage	Art. no.	
600-S1	230 V	28 511	
1250-S3	230 V	28 512	