

Lifting station *Aqualift S Compact*

The flexible version
for wastewater without sewage.

The *Aqualift S Compact* is the first lifting station in our range that can be converted comfortably from a Mono to a Duo system after floor slab installation. Yet that is not the only feature that makes the *Aqualift S Compact* so special: the free suspension and acoustic decoupling of the pump(s) also makes particularly quiet operation possible.

The *Aqualift S Compact* is available with float switch or pneumatic level measurement. The lifting station can also take up and discharge water additionally from the surface through the drain integrated in the black or tileable cover. It is delivered from the factory with either one or two pumps; the new GTF 500 and GTF 500 resistant (for aggressive wastewater such as heating condensate).



- 1 Lifting station 2 Extension section with flange 3 Cover with integrated inlet
4 Control unit

Maximum safety

The *Aqualift S Compact* is available with a pressure sensor *Tronic*, which measures the level of the wastewater precisely and reliably: as soon as the maximum water level is reached, the pump activates and pumps the water through a pressure pipe into the sewer.

Floor slab installation

The lifting station is almost invisible because it is installed in the floor slab. The integrated drain in the cover handles basement surface water. Even in the event of a pipe burst or flooding, the *Aqualift S Compact* continually pumps away the wastewater keeping the basement dry.

Installation in waterproof concrete

The KESSEL sealing kit for installation in waterproof concrete ensures reliable protection against moisture damage. The extension section with central flange and elastomeric waterproofing membrane enable implementation also in deeper installation situations.