

Accessories

Installation set

Art. no.

Installation set

Compatibility: For installation in a concrete floor *Aqualift F Compact* and *Aqualift S Compact*; for installation in waterproof concrete

Inclusive:

- 1 Extension section with central flange
- 2 Pressure pipe set Ø 32
- 3 Adapter (Ø 75/Ø 110 socket)
- 4 Seal insert
- 5 Casing
- 6 Puddle flange (2)



83 077

Extension sections

Art. no.


with centre flange

Compatibility: For installation in a concrete floor *Aqualift F Compact* and *Aqualift S Compact*

Additional function: For installation in waterproof concrete

Inclusive: Temporary construction debris cover, fully assembled, gasket set (counter flange made of polymer, screwed, elastomer sealing sheet made of NK/SBR Ø 800 mm)

Extension: Max. 360 mm



83 075


with flange and counter flange

Compatibility: For installation in a concrete floor *Aqualift F Compact* and *Aqualift S Compact*

Additional function: For connection to an on-site sealing sheet

Inclusive: Screws

Extension: Max. 140 mm (In case of deeper installation ensure maintenance capability!)




83 073

with gasket

Compatibility: For installation in a concrete floor *Aqualift F Compact* and *Aqualift S Compact*

Extension: Max. 180 mm (In case of deeper installation ensure maintenance capability!)




83 070

for deeper installation with flange

Compatibility: For installation in a concrete floor *Minilift S* (280 570X, 280 570S, 280 570XC and 280 570SC)

Inclusive: Gasket

Extension: Max. 147 mm (In case of deeper installation ensure maintenance capability!)



830 070

Pressure pipe set

Outer diameter Ø (mm)

Art. no.

Pressure pipe set

Compatibility: Ø 40 / Ø 50:

Aqualift F Compact, *Aqualift S Compact*
Ø 40: *Minilift S* (280 570X, 280 570S, 280 570XC and 280 570SC)

Inclusive: 5 m pressure pipe hose
Ø 40 (DN 32 mm)
Ø 50 (DN 40 mm)



Ø 40

28 040

Ø 50

28 062

Click adapter

Outer diameter Ø (mm)

Art. no.

Click adapter

Compatibility: For changeover to PE connection; for lifting station *Aqualift F Compact*, *Aqualift S Compact* and *Minilift S* (280 570X, 280 570S, 280 570XC and 280 570SC)



Ø 32

28 086