Accessories

Upgrade set			Art. no.
Alarm float switch	Compatibility: Can be combined with 230 V Comfort control units; for lifting station Aqualift F Compact Inclusive: Float switch, float switch bracket Cable length: 5 m	O ₁ o	28 016
	Compatibility: For use with 230 V and 400 V Comfort control units; for lifting station Aqualift F Mono/Duo Inclusive: Float switch, support plate, cover Cable length: 5 m		28 015
	Compatibility: For use with 230 V and 400 V Comfort control units Inclusive: Float switch, support plate, cover Cable length: 5 m		28 014

Cable extensions

for extension from 15 m or 25 m (cable length delivered: 5 m)

	Lifting station Aqualift F Compact Mono Aqualift S Compact Mono Aqualift S 100 Mono Aqualift S 100 Mono Tronic	Lifting station Aqualift F Compact Duo Aqualift S Compact Duo Aqualift S 100 Duo Tronic Aqualift S 200 Duo Tronic	Art. no.
Cable extension for probe (10 m)	Extension to 15 m: 1×80 889 Extension to 25 m: 2×80 889	Extension to 15 m: 1×80 889 Extension to 25 m: 2×80 889	80 889
Cable extension for pump (10 m)	Extension to 15 m: 1×80 891 Extension to 25 m: 2×80 891	Extension to 15 m: 2×80 891 Extension to 25 m: 4×80 891	80 891

Flexible pressure pipe connection		Outer diameter Ø (mm)	Art. no.	
for manual diaphragm pump	Compatibility: For PE pipe connections; for lifting station Aqualift F Basic, Aqualift F Mono / Duo and Aqualift F XL Inclusive: Two hose clamps Length: 200 mm		Ø 32	28 660
for ventilation	Compatibility: For PE pipe connections; for Aqualift F Basic, Aqualift F Mono / Duo and Aqualift F XL Inclusive: Two hose clamps Length: 200 mm		Ø 70	28 661
for connection adapter	Compatibility: For PE pipe connections;		Ø 90	28 662
and pressure pipes	for Aqualift F Mono / Duo and Aqualift F XL; Art. no. 28 663: Aqualift F Basic Inclusive: Two hose clamps Length: 200 mm		Ø 110	28 663