










Accessories

| Closure valves | | | Outer diameter Ø (mm) | Art. no. |
|------------------------------------|--|---|--------------------------|------------------|
| Closure valve, vertical | Compatibility: For lifting station <i>Aqualift F Basic</i> , <i>Aqualift F Mono / Duo</i> and <i>Aqualift F XL</i> Function: For the pressure pipe of KESSEL lifting stations with plastic fitting; for connection to pressure pipe, a KESSEL flange connector or adapter is required. Inclusive: Gasket, screw |  | Ø 90 | 28 715 |
| | Compatibility: For lifting station <i>Aqualift F Basic</i> , <i>Aqualift F Mono / Duo</i> and <i>Aqualift F XL</i> Function: For the pressure pipe of KESSEL lifting stations with plastic fitting Inclusive: With screwed flange adaptor, for connection to a standard flange DN 80 according to DIN 2501 (without sealing gasket and screw) |  | Ø 90 | 28 716 |
| Closure valve | Compatibility: With lateral pressure pipe for lifting stations <i>Aqualift F</i> |  | Ø 100 Ø 110 | 28 682 28 683 |
| | Compatibility: For installation on the inlet side (no pressure) for lifting stations <i>Aqualift F</i> |  | Ø 110 Ø 160 | 28 698 28 699 |
| | | | | |
| | | | | |
| Connection flange | | | Outer diameter Ø (mm) | Art. no. |
| in PE | Compatibility: For KESSEL plastic fittings; for lifting station <i>Aqualift F XL</i> |  | Ø 90 | 28 713 |
| | Compatibility: For KESSEL plastic fittings; for <i>Aqualift F Basic</i> and <i>Aqualift F XL</i> ; also in combination with closure valve Art. no. 28 715 Function: Spigot end for DN 100 pressure pipe connection |  | Ø 110 | 28 712 |
| Manual diaphragm pump 1 1/2 inch | | | | Art. no. |
| Manual diaphragm pump in cast iron | Compatibility: For manually pumping wastewater; for lifting station <i>Aqualift F Mono / Duo</i> and <i>Aqualift F XL</i> Inclusive: With a ball valve on inlet and outlet side |  | | 28 680 |
| Flange adaptor | | | Outer diameter Ø (mm) | Art. no. |
| in PE | Compatibility: From KESSEL fitting to standard flange; for lifting station <i>Aqualift F XL</i> |  | DN 80 | 28 714 |
| in cast iron | Compatibility: For use with cast iron pressure pipes; for lifting station <i>Aqualift F XL</i> Function: Adaptor from DN 80 to DN 100 Inclusive: Flange according to DIN 2501 |  | - | 28 068 |