

Accessories

		Outer diameter Ø (mm)	Art. no.
Backflow preventer			
in cast iron	<p>Compatibility: For lifting station <i>Aqualift F XL</i></p> <p>Inclusive: DN 80 flange according to DIN 2501, backflow preventer with flap and flap opening lever</p>	DN 80	28 021
			
Connection adaptor			
in cast iron	<p>Compatibility: For connection from lifting station <i>Aqualift F XL</i> to on-site pressure pipe. Fits PE pressure pipes</p> <p>Inclusive: Flange according to DIN 2501, single gasket</p> <p>Outer diameter: DN 80: OD 90 mm DN 100: OD 110 mm</p>	Ø 90	28 067
			
		Ø 110	28 020
			
Gate closure valve			
in cast iron	<p>Compatibility: For lifting station <i>Aqualift F XL</i></p> <p>Inclusive: DN 80 flange according to DIN 2501, gate closure valve including closure wheel</p>	DN 80	28 041
			
Y-Coupling			
in cast iron	<p>Compatibility: For lifting station <i>Aqualift F XL</i></p> <p>Inclusive: DN 80 (OD 80 mm) flange according to DIN 2501</p>	Ø 80	28 042
			
Sealing gasket			
Sealing gasket (rubber)	<p>Compatibility: Flange according to DIN 2501, for pressure pipe connections; for lifting station <i>Aqualift F XL</i></p>	DN 80 DN 100	28 043 28 044
			
Bolt set M16	<p>Compatibility: For Art. no. 28 043 and 28 044</p> <p>Inclusive: 4 bolts, 4 nuts, 8 washers</p>		28 078