202 **4.1 Bathroom drains**Catalogue EN 4.1 **KESSEL AG**

Modular system 100

For body drains Classic, The Superflat and Floordrain ME

Shower channel upper section

with cover in stainless steel AISI 304



Channel length Linearis Compact Art. no. in mm in stainless steel AISI 304 47 804S 300 Material: ABS, rim in stainless steel 450 47 805S Class: K.3 550 47 806S Cover: Can be reversed and tiled on site 650 47 807S Sealing water height: 50 mm 750 47 808S Drainage capacity: 0.6 l/sec (10 mm threshold) 850 47 809S Inclusive: Removable odour trap 47 810S 950 47 811S 1050 (remove from all drain bodies during 1150 47 812S installation), seeping water opening prepared, installation supports and waterproofing membrane

Variofix shallow bed upper sections

with covers in stainless steel



with design cover Kessel / Oval

in stainless steel AISI 304

Material: ABS, rim in stainless steel

Class: L 15

Tile thickness: 8 – 21 mm Cover: 120×120 mm

Anti-slip class design cover Kessel:

R9 according to DIN 51130; C according to DIN 51097

Inclusive: Waterproofing membrane

Kessel Art. no. 47 904 Oval Art. no. 47 905

Upper sections

with covers in stainless steel

















System 100

with design covers

in stainless steel AISI 304

Material: ABS, rim in stainless steel

Class: L 15 (Kessel, Oval) / K 3 (Spot, Slot)

Cover: 120×120 mm

Anti-slip class design cover Kessel:

R9 according to DIN 51130; C according to DIN 51097

Cover	Art. no.	Cover	
with <i>Lock & L</i>	<i>ift</i> System	witho	
1 AISI 304	27 201	1	
2 AISI 304	27 202	2	
3 AISI 304	27 221	3	
4 AISI 304	27 219	4	

Cover	Art. no.
without <i>Lock &</i>	<i>Lift</i> System
1 AISI 304	27 225
2 AISI 304	27 226
3 AISI 304	27 220
4 AISI 304	27 218

with slotted cover

in stainless steel AISI 304

Material: ABS, rim in stainless steel

Class: L 15


Cover: 138×138 mm

Art. no. 27 196 Art. no. 27 176, anti-slip

Drain bodies Classic in ABS

with / without removable odour trap









Lateral outlet / Vertical outlet Ø 50 / Ø 75

Sealing water height: 50 mm

Drainage capacity: 0.8 l/sec with 20 mm threshold

with removabl	e odour trap			without removable odour trap		p	
Lateral outlet	Art. no.	Vertical outlet	Art. no.	Lateral outlet	Art. no.	Vertical outlet	Art. no.
Ø 50	40 150	Ø 50	40 250	Ø 50	40 151	Ø 50	40 251
Ø 75	40 170	Ø 75	40 270	Ø 75	40 171	Ø 75	40 271

Drain body Floordrain ME in ABS

with removable odour trap





Three lateral inlets Ø 55, one lateral outlet Ø 82

Drainage capacity:

1.8 L/sec with 20 mm threshold Inclusive: Glue connection according to BS 5255.

DIN Push fit / DIN glue connection available as accessorie (page 203)

Art. no. 37 3001