

## Floor drain *Practicus*

with slotted cover in stainless steel AISI 304


System 125



TÜV Rheinland Germany type tested and monitored



Made in PP, with removable odour trap, sealing water height 50 mm, vertical outlet, with lip seal. Drainage capacity in l/sec with 20 mm / 10 mm threshold  
 Ø 110: 2.0 l/sec / 1.0 l/sec.  
 Installation area 350 × 350 mm  
 With upper section in ABS, with glue flange and counter flange, slotted cover 138 × 138 mm in stainless steel AISI 304, screwed, class K 3



Outer diameter Ø (mm)

Art. no.

Ø 110

45 218.11

## Floor drain *Practicus*

with slotted cover in stainless steel AISI 304


System 125



TÜV Rheinland Germany type tested and monitored



Made in PP, with removable odour trap, sealing water height 50 mm, vertical outlet, with lip seal. Drainage capacity in l/sec with 20 mm / 10 mm threshold 2.0 l/sec / 1.0 l/sec.  
 Installation area 180 × 180 mm  
 With upper section in ABS, slotted cover 120 × 120 mm in stainless steel AISI 304, class K 3



Outer diameter Ø (mm)

Art. no.

Ø 50

45 250.20

Ø 75

45 270.20

Ø 110

45 210.20