238 **4.2 Floor drains** Catalogue EN 4.1 **KESSEL AG**

System 125 Accessories Ecoguss and Practicus **Dimensions Flanges** in mm Art. no. Clip flange Compatibility: For combination with drain 280×280 44 703 bodies and extension sections; for floor drain *Ecoguss* and *Practicus* **Inclusive:** Factory-mounted waterproofing membrane in accordance with EN 1253-1 and DIN 18534-1-W3-I Ø 348 Glue flange 48 410 Compatibility: For combination with drain with counter flange bodies and extension sections; also for compound seal; for floor drain ${\it Ecoguss}$ and Practicus Material: ABS without connection Compatibility: For combination with drain Ø 268 48 409 Ø268 flange bodies and extension sections; for floor drain *Ecoguss* and *Practicus* Material: ABS **Pressure sealing Compatibility:** For combination with drain Ø 273 48 407 Ø 273 bodies and extension sections; for floor flange drain *Ecoguss* and *Practicus* Material: Stainless steel AISI 304 **Inclusive:** Seeping water opening Waterproofing membranes Art. no. Waterproofing membrane Compatibility: Art. no. 48 410 48 651 48 650 2 component adhesive **Compatibility:** For gluing of KESSEL waterproofing 48 981 **Elastomer waterproofing** Compatibility: Art. no. 48 407 Material: NBR membrane Intermediate section Art. no. with glue flange Compatibility: Shallow bed gasket 48 900 Inclusive: With non-mounted waterproofing membrane according to EN 1253-1 and DIN 18534-1-W3-I **Extension sections** Art. no.

2.Xtoriolori deditioni				Al C. III.
without lateral inlet	Compatibility: For floor drain <i>Ecoguss</i> and <i>Practicus</i> Material: PP Inclusive: Lip seal	9	Ø150 Ø125	48 987
with lateral inlet Ø 50	Compatibility: For floor drain <i>Ecoguss</i> and <i>Practicus</i> Material: PP Inclusive: Lip seal		Ø150 Ø125 158	48 989