


Modular system 125 Ferrofix

Floor drains Ferrofix in stainless steel AISI 304

Variofix shallow bed upper sections







with slotted cover

Material: ABS, rim in stainless steel

Class: L 15

Tile thickness: max. 16 mm

Cover: 150×150 mm, anti-slip, screwed Inclusive: Waterproofing membrane

Art. no. 48 907

with slotted cover*

Material: ABS, rim in stainless steel

Class: L 15

Cover: 146×146 mm, anti-slip **Inclusive:** Waterproofing membrane

Art. no. 48 965

with slotted cover

Material: ABS, rim in stainless steel

Class: K 3

Tile thickness: max. 18 mm Cover: 150×150 mm, screwed Inclusive: Waterproofing membrane

Art. no. 48 963

Upper sections with glue flange*









200 - 50

with slotted cover

Class: K 3

Cover: 146×146 mm

Art. no. 54 919

with anti-slip drain cover

Class: L 15 / M 125 Cover: 146×146 mm

Art. no. 54 915

with anti-slip drain cover*

Class: L 15 / M 125 Cover: 200×200 mm

Art. no. 54 917

Sanitary upper sections*







Upper sections for PVC floorings*





with gas and liquid tight cover

Class: L 15

Cover: 150×150 mm

Note: Custom made (delivery time on request), cover available with removal

threads

Art. no. 59 011

with gas and liquid tight cover

Class: L 15

Cover: 150×150 mm, screwed, backwater-proof seal up to 0.5 bar

Note: Custom made (delivery time on request),

cover available with removal threads

Art. no. 59 013

with cover

Class: L 15

Tile thickness: 1 – 4 mm Cover: Ø 133 mm, screwed

Note: Custom made (delivery time on request)

Art. no. 59 192

Clean outs*









with rim and closed cover

Material: ABS, cover in stainless steel

Class: L 15

Cover: 150×150 mm, screwed, with gasket

Art. no. 54 920

*Not for combination with The Ultraflat 54 / 79 drain bodies

with closed cover

Class: L 15

Cover: 150×150 mm, screwed odour-tight, gasket, backwater-proof seal up to 0.5 bar

Art. no. 54 912

with closed cover plate

Class: L 15

Cover: 150×150 mm, screwed, gastight, backwater-proof seal up to 0.5 bar, tileable

Art. no. 54 910