


### Clean-out *Ferrofix* Ø 125

System 125

for direct access to piping

Upper section made of stainless steel AISI 304. With closed, screw-type cover plate 150×150 mm made of stainless steel AISI 304, class L 15, screwed odour-tight, with gasket, with a backwater-proof seal up to 0.5 bar

**Compatibility:** Not in combination with drain bodies *The Ultraflat 54* and *79*



Connection Ø	Art. no.
Ø 125	54 912


### Clean-out *Ferrofix* Ø 125

System 125

for direct access to piping

Upper section made of stainless steel AISI 304. With closed, screw-type cover plate 150×150 mm made of stainless steel AISI 304, class L 15, gastight and a backwater-proof seal up to 0.5 bar, tileable

**Compatibility:** Not in combination with drain bodies *The Ultraflat 54* and *79*



Connection Ø	Art. no.
Ø 125	54 910

### Sanitary upper section *Ferrofix* Ø 125


System 125

for direct access to piping

Upper section made of stainless steel AISI 304. With gas and liquid tight cover 150×150 mm made of stainless steel AISI 304, class L 15

**Compatibility:** Not in combination with drain bodies *The Ultraflat 54* and *79*

**Note:** Custom made (delivery time on request), cover available with removal threads



Connection Ø	Art. no.
Ø 125	59 011

### Sanitary upper section *Ferrofix* Ø 125


System 125

for direct access to piping

Upper section made of stainless steel AISI 304. With gas and liquid tight cover 150×150 mm made of stainless steel AISI 304, class L 15, screwed, backwater-proof seal up to 0.5 bar

**Compatibility:** Not in combination with drain bodies *The Ultraflat 54* and *79*

**Note:** Custom made (delivery time on request), cover available with removal threads



Connection Ø	Art. no.
Ø 125	59 013