

# Basement drains without backwater valve

The drain for uncomplicated applications.

Basement drains without backwater valves are ideally suitable for basements that lie above the backwater level, meaning they are not at risk of backwater flooding. We supply our basement drains without backwater valves with or without odour trap and / or sludge bucket as well as with lateral or vertical outlet.

## Odour trap

We offer different drains with integrated odour traps to protect against unpleasant odours from the sewer. Many drains can also be equipped with our Multistop waterless odour trap, whose tightly sealing flap provides additional protection against foam and vermin.

## Basement drain *Practicus*

For installation in a concrete floor / slab

TÜV Rheinland Germany type tested and monitored



EN 1253-1

Made in PP. With removable odour trap, with lip seal and protective cover or use during construction.

Drainage capacity in l/sec with 20 mm / 10 mm threshold 1.6 l/sec / 1.1 l/sec.

Installation area:

lateral outlet: 220 × 180 mm

vertical outlet: 180 × 180 mm

With upper section in ABS

### Cover:

Slotted cover 138 × 138 mm in ABS, black, class K 3

➤ **Accessories:** see page 275 – 279



Illustration shows Art. no. 45 110.40 (lateral outlet)




Illustration shows Art. no. 45 110.40 (lateral outlet)




Illustration shows Art. no. 45 210.40 (vertical outlet)



Outer diameter Ø (mm)	Art. no.
<b>Lateral outlet</b>	
Ø 110	<b>45 110.40</b>
<b>Vertical outlet</b>	
Ø 110	<b>45 210.40</b>