

Flat-roof drains in *Ecoguss*

System 200

with pressure sealing flange in *Ecoguss*


TÜV Rheinland Germany type tested and monitored



EN 1253-1 / DIN 1986-100

Vertical outlet, with single seal, pressure sealing flange in *Ecoguss*, gravel trap.

Installation area: Ø 227 mm



Outer diameter Ø (mm)	H in mm	Art. no.
-----------------------	---------	----------

Without heating

Ø 78	96.5	48 370
Ø 110	93	48 310
Ø 125	93	48 312

With heating

Ø 78	96.5	48 370.03
Ø 110	93	48 310.03
Ø 125	93	48 312.03

Flat-roof drains in *Ecoguss*

System 200

with pressure sealing flange in *Ecoguss*


TÜV Rheinland Germany type tested and monitored



EN 1253-1 / DIN 1986-100

Vertical outlet, with double seal for installation in waterproof concrete, pressure sealing flange in *Ecoguss* and counter flange, upper section in *Ecoguss* Ø 200, gravel trap.

Installation area: Ø 227 mm



Outer diameter Ø (mm)	H in mm	Art. no.
-----------------------	---------	----------

Without heating

Ø 78	96.5	48 370.01
Ø 110	93	48 310.01
Ø 125	93	48 312.01

With heating

Ø 78	96.5	48 370.02
Ø 110	93	48 310.02
Ø 125	93	48 312.02