Data sheet

Lifting station Aqualift XL 300l Duo, SPF 1400-S3, Backflow preventer

Article information
article number: 11014
EAN code: 4026092056813
Price group: 50

Product advantages
- Different performance classes available
- Pressure sensor for reliable pneumatic level measurement
- Maximum operating reliability due to intelligent control unit

Description
The lifting station for faecal and faecal-free wastewater is equipped with one or two submersible pumps and a backflow preventer. The collection tank made of permanently resistant polymer (PE) offers universal connection options and has a screwed access cover.

General features

Colour	black
Standard	EN 12050-1
Type of wastewater	with sewage
Installation situation	free-standing installation
System type	Duo

Version

Type of system	duo pump
Shut-off valve	without shut-off valve
Backflow preventer	integrated
Pressure pipe connection	vertical

Dimensions

Net weight	182.67 kg
Gross weight	202.67 kg
Packaging dimension: length	1650 mm
Packaging dimension: width	1150 mm
Packaging dimension: height	890 mm

Tank/drain body

Tank volume	300.00 l

Pumping device

Pump	SPF 1400-S3
Number of pumps	2
Operating mode	S3
Impeller type	Multi-vane impeller
Free passage	40 mm
Length of mains cable for pump	5 m

Pumping capacity



Control

Control unit	Comfort
Operating voltage	230 V
Level measurement instrument	Immersion pipe
Type of level measurement	pneumatic