Data sheet

Lifting station Aqualift XL 200 L Duo, SPF 5600

Article information
article number: 11073
EAN code: 4026092057407
Price group: 50

Product advantages
- Different performance classes available
- Pressure sensor for reliable pneumatic level measurement
- Maximum operating reliability due to intelligent control unit

Description
The lifting station for faecal and faecal-free wastewater is equipped with one or two submersible pumps and a backflow preventer. The collection tank made of permanently resistant polymer (PE) offers universal connection options and has a screwed access cover.

General features

Colour	black
Standard	EN 12050-1
Type of wastewater	with sewage
Installation situation	free-standing installation
System type	Duo

Version

Type of system	duo pump
Shut-off valve	without shut-off valve
Backflow preventer	integrated
Pressure pipe connection	vertical

Dimensions

Net weight	215 kg
Gross weight	235 kg
Packaging dimension: length	1650 mm
Packaging dimension: width	1150 mm
Packaging dimension: height	890 mm

Tank/drain body

Tank volume	200.00 l

Pumping device

Pump	SPF 5600
Number of pumps	2
Weight, pump	38 kg
Connection type	Direct connection
Operating voltage	400 V
Mains frequency	50 Hz
Protection class	I
Insulation class	F
Protection class (pump)	IP 68 (3m/48h)
Temperature monitoring	integrated
Max. temperature (permanent) of conveyed material	40 °C
Max. pumping capacity	60 m³/h
Max. pumping height	28 m
Speed	2800 U/min
Power P1	5.7 kW
Power P2	4.8 kW
Operating mode	S3 - 30 %
Type of pump connection cable	H07RN8-F 6G 1 mm²
Impeller type	Multi-vane impeller
Free passage	40 mm
Length of mains cable for pump	5 m
Rated current	9,1| A

Pumping capacity



Control

Control unit	Comfort
Operating voltage	400 V
Protection class control unit	IP 54
Self-diagnosis system (SDS)	yes
Battery buffering	yes
Multi-line display	yes
Log book function	yes
Potential-free contact	yes
Alarm sensor	Immersion pipe
Level measurement instrument	Immersion pipe
Type of level measurement	pneumatic
Connection type	Direct connection
Length of mains cable for control unit	0 m
GSM interface	yes
Motor protection switch	yes