Data sheet

Comfort control unit 400V, Mono, 2.5-4.0 A, direct connection

Article information
article number: 28759
EAN code: 4026092054598
Price group: 90

Product advantages
- Self-diagnosis system (SDS)
- Potential-free contact for faults/warnings
- Reminder for when maintenance is due

Description
Komfort control unit for lifting stations or pumping stations. Suitable for 400 V single stations. Optional connection option for float switches, conductivity probes and level probe on the terminal strip. User-friendly menu navigation in multi-line display. Menu navigation in six languages. Simple selection of the system to be connected with preset, system-specific operating parameters. Display of the current measured values. Simple adjustment of the function-related parameters, with integrated operating hour counter. With self-diagnosis system (SDS) for monitoring pump, sensors and battery back-up. Improper installation or operating faults trigger an optical and acoustic alarm signal. Forwarding of a collective fault and alarm signals via optional potential-free contact or integrated serial interface for GSM modem.

General features

Colour	grey
System type	Mono

Version

Series	ab 03/2010
Type of system	Single unit

Dimensions

Net weight	2.47 kg
Gross weight	3.19 kg
Packaging dimension: length	330 mm
Packaging dimension: width	250 mm
Packaging dimension: height	210 mm

Pumping device

Connection type	Direct connection

Control

Control unit	Comfort
Operating voltage	400 V
Rated current (max.)	2,5|4 A
Protection class control unit	IP 54
Self-diagnosis system (SDS)	yes
Battery buffering	yes
Multi-line display	yes
Log book function	yes
Potential-free contact	yes
USB interface	no
Connection type	Direct connection
Length of mains cable for control unit	0 m
GSM interface	yes
Motor protection switch	yes