Data sheet

Comfort control unit 400V, Duo, 2x4.0-6.3 A direct connection

Article information

article number: 28763
EAN code: 4026092054628
Price group: 20

Product advantages

- Self-diagnosis system (SDS)
- Potential-free contact for faults/warnings
- Reminder for when maintenance is due

Description

Comfort control unit for lifting stations or pumping stations. Suitable for 400 V double stations. Optional connection options for float switches, conductivity probes, and level probes on the terminal strip. User-friendly menu navigation on the multi-line display. Menu navigation in six languages. Simple selection of the system to be connected with preset, system-specific operating parameters. Display of current measured values. Simple adjustment of function-relevant parameters, with integrated operating hour counter. With self-diagnosis system (SDS) for monitoring pump, sensors and battery back-up. Improper installation or operating faults trigger an optical and acoustic alarm signal. Forwarding of a collective fault and alarm signal via optional potential-free contact or integrated serial interface for a GSM modem.

General features

Colour	grey
System type	Duo

Version

Series	ab 03/2010
Type of system	duo pump

Dimensions

Net weight	5.06 kg
Gross weight	5.39 kg
Packaging dimension: length	390 mm
Packaging dimension: width	190 mm
Packaging dimension: height	310 mm

Pumping device

Connection type	Direct connection

Control

Control unit	Comfort
Motor protection switch	yes
Protection class control unit	IP 54
Connection type	Direct connection
Length of mains cable for control unit	0 m
Potential-free contact	yes
GSM interface	yes
USB interface	no
Log book function	yes
Multi-line display	yes
Battery buffering	yes
Self-diagnosis system (SDS)	yes
Rated current	4|6,3 A