Data sheet

Practicus floor drain press.seal. DN 70, horizontal, Slotted grating



Article information

article number: 45179.11
EAN code: 4026092033029
Price group: 10

Product advantages

- Hygiene: hygienic, absolutely corrosion-free and durable material
- Sound insulation: outstanding sound insulation effect confirmed by the Fraunhofer Institute

Description

The Practicus polymer floor drain is used for point drainage and is equipped with a pressure sealing flange as well as a removable odour trap, a lip seal and a temporary protective cover. Including telescopic height-adjustable upper section made of ABS. The drain meets particular sound insulation requirements in accordance with the measurements of the Fraunhofer Institute in Stuttgart. The pressure sealing flange with bolts and screws made of stainless steel is used for the clamping or welding of bitumen and polymer bitumen sheets as well as for polymer and elastomer sealing sheets. The outlet socket is suitable for connection to SML cast iron pipes. With connection option for equipotential bonding.

General features

Standard	EN 1253-1
Nominal size (DN)	70
Outer diameter (OD)	75 mm
Odour trap	included
Sustainable	through the use of recycled material

Version

System	125
Waterproofing layer on the upper section	Connection flange
Waterproofing layer on the drain body	Press sealing flange (suitable for creating watertight seals)
Sealing water height	50 mm
Discharge rate (l/s) with 20 mm threshold	1.3

Dimensions

Vertical adjustment	|
Net weight	1.94 kg
Gross weight	2.57 kg
Type of height adjustability	vertically adjustable upper section
Length	273 mm
Width	273 mm
Packaging dimension: length	400 mm
Packaging dimension: width	300 mm
Packaging dimension: height	400 mm

Tank/drain body

Number of outlets	1
Material of drain body	PP
Socket version	lateral

Coverage features

Type of cover	Slotted cover
Cover material	Stainless steel 14301
Colour of cover	silver
Width of cover	138 mm
Height of cover	16 mm
Length of cover	138 mm
Frame material	ABS
Locking	screwed
Load class	K 3 (EN 1253-1)
Grating design	Kessel
Rim width	150 mm
Rim length	150 mm
Upper section	vertically adjustable
Upper section material	ABS