Data sheet

Practicus floor drain press.seal. DN 100, vertical, Design grating



Article information

article number: 45219.63
EAN code: 4026092052594
Price group: 10

Product advantages

- Hygiene: hygienic, absolutely corrosion-free and durable material
- Fire protection: combinable with the Fire-Kit for fire and smoke protection
- Sound insulation: outstanding sound insulation effect confirmed by the Fraunhofer Institute

Description

The Practicus polymer floor/roof drain is designed for point drainage and is fitted with a pressure sealing flange, a removable odour trap, a lip seal and a temporary protective cover. Includes a vertically adjustable, height-adjustable upper section made of polymer. The drain meets specific sound insulation requirements as measured by the Fraunhofer Institute in Stuttgart. The pressure sealing flange is suitable for use with standard waterproofing layers in accordance with the installation instructions, as well as flame-applied bituminous membranes. For watertight waterproofing layers, only waterproofing sheets tested by the manufacturer may be used.

General features

Standard	EN 1253-1
Nominal size (DN)	100
Outer diameter (OD)	110 mm
Odour trap	included
Approval	Z-19.53-2414,Z-19.53-2414_V,Z-19.17-1719,Z-19.17-1719_V

Version

System	125
Waterproofing layer on the upper section	Connection flange
Waterproofing layer on the drain body	Press sealing flange (suitable for creating watertight seals)
Sealing water height	50 mm
Discharge rate (l/s) with 20 mm threshold	1.9

Dimensions

Vertical adjustment	|
Net weight	2.81 kg
Gross weight	3.44 kg
Type of height adjustability	vertically adjustable upper section
Length	273 mm
Width	273 mm
Packaging dimension: length	400 mm
Packaging dimension: width	300 mm
Packaging dimension: height	400 mm

Tank/drain body

Number of outlets	1
Connection inlet/outlet sockets	The outlet spigot is suitable for connection to SML pipes.
Material of drain body	PP
Socket version	vertical

Coverage features

Type of cover	Design cover
Cover material	Stainless steel 14301
Colour of cover	silver
Width of cover	120 mm
Height of cover	16 mm
Length of cover	120 mm
Frame material	Stainless steel 14301
Locking	Lock & Lift
Load class	L 15 (EN 1253-1)
Grating design	Kessel
Slip resistance class	R9 according to DIN 51130; C according to DIN 51097
Rim width	132 mm
Rim length	132 mm
Upper section	vertically adjustable
Upper section material	ABS