Data sheet

Practicus floor/roof drain DN 70, vertical, Slotted grating screwed



Article information

article number: 45270.11
EAN code: 4026092032930
Price group: 10

Product advantages

- Hygiene: hygienic, absolutely corrosion-free and durable material
- Fire protection: combinable with the Fire-Kit for fire and smoke protection
- Sound insulation: outstanding sound insulation effect confirmed by the Fraunhofer Institute

Description

The Practicus floor drain is used for point drainage and is equipped with a connection flange as well as a removable odour trap, a lip seal and a temporary protective cover. Including telescopic height-adjustable upper section made of ABS. The drain meets particular sound insulation requirements in accordance with the measurements of the Fraunhofer Institute in Stuttgart. The outlet socket is suitable for connection to SML cast iron pipes. With connection option for equipotential bonding.

General features

Standard	EN 1253-1
Nominal size (DN)	70
Outer diameter (OD)	75 mm
Approval	Z-19.53-2414,Z-19.53-2414_V,Z-19.17-1719,Z-19.17-1719_V
Odour trap	included

Version

System	125
Waterproofing layer on the upper section	Connection flange
Waterproofing layer on the drain body	Connection flange
Sealing water height	50 mm
Discharge rate (l/s) with 20 mm threshold	2

Dimensions

Vertical adjustment	|
Net weight	1.42 kg
Gross weight	1.96 kg
Cutout dimension, width	180 mm
Cutout dimension, length	180 mm
Type of height adjustability	vertically adjustable upper section
Length	135 mm
Width	135 mm
Packaging dimension: length	390 mm
Packaging dimension: width	190 mm
Packaging dimension: height	310 mm

Tank/drain body

Number of outlets	1
Material of drain body	PP
Socket version	vertical

Coverage features

Type of cover	Slotted cover
Cover material	Stainless steel 14301
Colour of cover	silver
Width of cover	138 mm
Height of cover	16 mm
Length of cover	138 mm
Surface	Polished SST
Frame material	ABS
Locking	screwed
Load class	K 3 (EN 1253-1)
Grating design	Kessel
Rim width	150 mm
Rim length	150 mm
Upper section	vertically adjustable
Shape of upper section	square
Upper section material	ABS