Data sheet

Shower channel Linearis Compact L: 850 mm, DN 50, WaD, 304 SST cov., K 3





Article information

article number: 45600.64M
EAN code: 4026092078921
Price group: 10

Product advantages

- Individual design with reversible stainless steel insert
- Low installation depth
- Ready-to-install complete set

Description

The Linearis Compact shower channel with welded on drain body made of ABS is suitable for indoor linear drainage. If inserted upside down, the stainless steel insert can be tiled individually. Including prepared seepage water openings and odour trap.

General features

Nominal size (DN)	50
Outer diameter (OD)	50 mm
Odour trap	included

Version

System	125
Seepage opening	prepared
Waterproofing layer on the upper section	Factory-fitted sealing collar (WaD) according to DIN 18534
Water exposure class in accordance to DIN 18534-1 (up to and including)	W3-I
Sealing water height	22 mm
Discharge rate (l/s) with 10 mm threshold	0.6
Discharge rate (l/s) with 20 mm threshold	0.7
Discharge rate (l/s) without threshold	0.5 mm

Dimensions

Net weight	2.28 kg
Gross weight	2.8 kg
Outer dimension, length	915 mm
Installation depth	80|140 mm
Width	191 mm
Height	80 mm
Packaging dimension: length	1280 mm
Packaging dimension: width	260 mm
Packaging dimension: height	130 mm

Tank/drain body

Number of outlets	1
Material of drain body	ABS

Coverage features

Type of cover	Stainless steel cover
Cover material	Stainless steel 14301
Colour of cover	silver
Frame material	Stainless steel 14301
Load class	K 3 (EN 1253-1)
Grating design	optionally tileable
Rim width	66 mm
Rim length	850 mm
Max. flooring height	15 mm
Shape of upper section	square
Upper section material	ABS