Data sheet

Roof drain Double press fl., DN 100, with leaf trap

Article information

article number: 45970
EAN code: 4026092029718
Price group: 10

Product advantages

Description

The roof drain for flat roof surfaces is used for point drainage and is equipped with a pressure sealing flange as well as a gravel trap. The recyclable composite material Ecoguss fulfils the highest sound protection requirements, is resistant to aggressive media, can withstand temperatures up to 400 degrees Celsius and has a permanently corrosion-free surface. Note: Please consult the KESSEL Service Centre for trapezoidal roof areas greater than 2500 sqm.

General features

Nominal size (DN)	100
Outer diameter (OD)	110 mm

Version

System	100
Heating	without
Waterproofing layer on the drain body	Press sealing flange (suitable for creating watertight seals)

Dimensions

Vertical adjustment	40|80 mm
Net weight	2.34 kg
Gross weight	3.1 kg
Diameter	246 mm
Cutout dimension, width	180 mm
Cutout dimension, length	180 mm
Type of height adjustability	vertically adjustable upper section
Length	246 mm
Width	246 mm
Packaging dimension: length	490 mm
Packaging dimension: width	275 mm
Packaging dimension: height	495 mm

Tank/drain body

Material of drain body	PP

Coverage features

Type of cover	Leaf trap
Cover material	Polymer
Colour of cover	black
Width of cover	120 mm
Height of cover	80 mm
Length of cover	120 mm
Shape of upper section	round
Upper section material	PP