Data sheet

Ecoguss drain body DN 100, Horizontal outlet



Article information

article number: 48311
EAN code: 4026092033272
Price group: 40

Product advantages

- High-tech Ecoguss composite material
- Highest fire protection standards
- Scientifically confirmed sound protection effect

Description

The Ecoguss drain body, in combination with an upper section made of stainless steel, Ecoguss and recycled polymer, is used for point drainage and is equipped with a removable odour trap and a construction period protection cover.

The recyclable composite material Ecoguss fulfils the highest sound insulation requirements, is permanently resistant to 350 aggressive media according to the resistance list, is temperature-resistant and has a permanently corrosion-free surface. It can be flame-treated for short periods from 100 to 400 degrees Celsius.

The pressure sealing flange with stainless steel bolts and screws is used for clamping or welding on bitumen and polymer bitumen sheets as well as polymer and elastomer waterproofing sheets. Only waterproofing sheets tested by the manufacturer may be used for waterproofing layers. The outlet spigot is suitable for connection to SML cast iron pipes. With connection option for equipotential bonding.

General features

Standard	EN 1253-1
Nominal size (DN)	100
Outer diameter (OD)	110 mm
Odour trap	included

Version

System	125
Waterproofing layer on the drain body	Connection flange
Sealing water height	50 mm

Dimensions

Vertical adjustment	|
Net weight	1.05 kg
Gross weight	1.16 kg
Diameter	135 mm
Height	132 mm
Packaging dimension: length	200 mm
Packaging dimension: width	200 mm
Packaging dimension: height	175 mm

Tank/drain body

Number of outlets	1
Material of drain body	Ecoguss resistant
Socket version	lateral