Data sheet

Roof drain Ecoguss Press. fl., waterpr conc, DN 70, w- htg

Article information

article number: 48370.02
EAN code: 4026092039342
Price group: 40

Product advantages

- Made of recyclable composite
- Permanently corrosion-free surface

Description

The Ecoguss roof drain for flat roof surfaces is used for point drainage and is equipped with a pressure sealing flange as well as a gravel trap. The recyclable composite material Ecoguss fulfils the highest sound protection requirements, is resistant to aggressive media, can withstand temperatures up to 400 degrees Celsius and has a permanently corrosion-free surface. The pressure sealing flange with bolts and screws made of stainless steel is used for the clamping or welding of bitumen and polymer bitumen sheets as well as for polymer and elastomer sealing sheets. Only the sealing sheets tested by the manufacturer may be used for watertight seals. Separate equipotential bonding is not necessary. Note: Please consult the KESSEL Service Centre for trapezoidal roof areas greater than 2500 sqm.

General features

Standard	EN 1253
Nominal size (DN)	70
Outer diameter (OD)	78 mm

Version

System	200
Heating	with
Waterproofing layer on the drain body	Press sealing flange (suitable for creating watertight seals)

Dimensions

Vertical adjustment	40|140 mm
Net weight	5.72 kg
Gross weight	6.27 kg
Diameter	365 mm
Cutout dimension, width	227 mm
Cutout dimension, length	227 mm
Type of height adjustability	vertically adjustable upper section
Length	365 mm
Width	365 mm
Packaging dimension: length	425 mm
Packaging dimension: width	425 mm
Packaging dimension: height	350 mm

Tank/drain body

Material of drain body	Ecoguss

Coverage features

Type of cover	Gravel trap
Cover material	Polymer
Colour of cover	black
Shape of upper section	round
Upper section material	Ecoguss