

Data sheet

Parking deck drain, Ecoguss DN 125, round, Connection polymer pipe



Article information

article number: 48504
 EAN code: 4026092036136
 Price group: 40

Product advantages

- Breakproof & load resistant
- withstand temperatures up to 400 degrees Celsius

Description

The Ecoguss parking deck drain is used for point drainage and is equipped with a sludge bucket. The recyclable composite material Ecoguss is temperature resistant and has a permanently corrosion-free surface. The outlet socket is suitable for connection to SML cast iron pipes. Separate equipotential bonding is not necessary. For products with pressure sealing flange: The pressure sealing flange with bolts and screws made of stainless steel is used for the clamping or welding of bitumen and polymer bitumen sheets as well as for polymer and elastomer sealing sheets. Only membranes tested by the manufacturer may be used for watertight seals. The outlet socket is suitable for connection to SML cast iron pipes. With connection option for equipotential bonding. It can be exposed to flames for short periods, 100 up to 400 degrees Celsius.

General features

Standard	EN 1253-2
Nominal size (DN)	125
Outer diameter (OD)	125 mm

Version

System	125
Contents of sludge trap	yes
Waterproofing layer on the drain body	Connection flange
Discharge rate (l/s) with 20 mm threshold	4.5

Dimensions

Net weight	2.37 kg
Gross weight	2.75 kg
Diameter	290 mm
Cutout dimension, width	300 mm
Cutout dimension, length	300 mm
Length	290 mm
Width	290 mm
Height	196 mm
Packaging dimension: length	340 mm
Packaging dimension: width	340 mm
Packaging dimension: height	215 mm

Tank/drain body

Material of drain body	Ecoguss Heavy Duty
Socket version	vertical

Coverage features

Type of cover	Round slotted cover
Cover material	Ecoguss
Colour of cover	black
Width of cover	234 mm
Length of cover	234 mm
Surface	EDM
Frame material	Ecoguss
Locking	Lock & Lift
Load class	B 125 (EN 124)
Rim width	247 mm
Rim length	247 mm
Shape of upper section	round
Contents of sludge trap	yes