Data sheet

# Ecoguss drain body glued flange, DN 100, Horizontal outlet




## Article information
article number: 48511
EAN code: 4026092032589
Price group: 40

## Product advantages
- High-tech Ecoguss composite material
- Highest fire protection standards
- Scientifically confirmed sound protection effect

## Description
The Ecoguss drain body, in combination with an upper section made of stainless steel, Ecoguss and recycled polymer, is used for point drainage and is equipped with a removable odour trap and a construction period protection cover.

The recyclable composite material Ecoguss fulfils the highest sound insulation requirements, is permanently resistant to 350 aggressive media according to the resistance list, is temperature-resistant and has a permanently corrosion-free surface. It can be flame-treated for short periods from 100 to 400 degrees Celsius.

The glued flange with stainless steel bolts and screws is used for clamping or welding on bitumen and polymer bitumen sheets as well as polymer and elastomer waterproofing sheets. Only waterproofing sheets tested by the manufacturer may be used for waterproofing layers. The outlet spigot is suitable for connection to SML cast iron pipes. With connection option for equipotential bonding.

## General features

| | |
|---|---|
| Standard | EN 1253-1 |
| Nominal size (DN) | 100 |
| Outer diameter (OD) | 110 mm |
| Odour trap | included |

## Version

| | |
|---|---|
| System | 125 |
| Waterproofing layer on the drain body | Adhesive flange (suitable for moisture barriers) |
| Sealing water height | 50 mm |

## Dimensions

| | |
|---|---|
| Vertical adjustment | \| |
| Net weight | 1.47 kg |
| Gross weight | 1.97 kg |
| Diameter | 348 mm |
| Height | 145 mm |
| Packaging dimension: length | 360 mm |
| Packaging dimension: width | 360 mm |
| Packaging dimension: height | 175 mm |

## Tank/drain body

| | |
|---|---|
| Number of outlets | 1 |
| Material of drain body | Ecoguss resistant |
| Socket version | lateral |