


Data sheet

Ecoguss drain body glued flange, DN 50, Vertical outlet



Article information

article number: 48658
 EAN code: 4026092033333
 Price group: 40

Product advantages

- High-tech Ecoguss composite material
- Highest fire protection standards
- Scientifically confirmed sound protection effect

Description

The Ecoguss base body is used in combination with an attachment piece for point drainage, and is equipped with a removable odor trap, and a protective cover for the construction period. The recyclable composite material Ecoguss meets the highest noise protection requirements, is temperature-resistant, resistant to aggressive media, and has a permanently corrosion-free surface. It is also briefly flammable from 100 to 400 degrees Celsius. The glued flange with a flange width of 50 mm is suitable for connecting waterproofing layers in accordance with DIN 18534, for all waterproofing classes. The loose flange is used for clamping polymer and elastomer sealing sheets as well as for cold bitumen seals and is therefore only suitable for use with moisture barriers.

The outlet socket is suitable for connection to SML cast iron pipes. Separate equipotential bonding is not necessary.

General features

Standard	EN 1253-1
Nominal size (DN)	50
Outer diameter (OD)	58 mm
Approval	Z-19.53-2414,Z-19.53-2414_V,Z-19.17-1719,Z-19.17-1719_V
Odour trap	included

Version

System	125
Waterproofing layer on the drain body	Adhesive flange (suitable for moisture barriers)
Sealing water height	50 mm

Dimensions

Vertical adjustment	
Net weight	1.31 kg
Gross weight	1.9 kg
Diameter	348 mm
Height	205 mm
Packaging dimension: length	360 mm
Packaging dimension: width	360 mm
Packaging dimension: height	250 mm

Tank/drain body

Number of outlets	1
Material of drain body	Ecoguss resistant
Socket version	vertical