Data sheet

Ecoguss drain body glued flange, DN 70, Vertical outlet



Article information

article number: 48678
EAN code: 4026092032633
Price group: 40

Product advantages

- High-tech Ecoguss composite material
- Highest fire protection standards
- Scientifically confirmed sound protection effect

Description

The Ecoguss drain body, in combination with an upper section made of stainless steel, Ecoguss and recycled polymer, is used for point drainage and is equipped with a removable odour trap and a construction period protection cover.

The recyclable composite material Ecoguss fulfils the highest sound insulation requirements, is permanently resistant to 350 aggressive media according to the resistance list, is temperature-resistant and has a permanently corrosion-free surface. It can be flame-treated for short periods from 100 to 400 degrees Celsius.

The glued flange with a flange width of 50 mm is suitable for connecting joint seals in accordance with DIN 18534 for all water exposure classes. The loose flange is used for clamping polymer and elastomer waterproofing sheets as well as cold bitumen seals and is therefore only suitable for use with moisture barriers.

The outlet spigot is suitable for connection to SML cast iron pipes. With connection option for equipotential bonding.

General features

Standard	EN 1253-1
Nominal size (DN)	70
Outer diameter (OD)	78 mm
Odour trap	included
Approval	Z-19.53-2414,Z-19.53-2414_V,Z-19.17-1719,Z-19.17-1719_V

Version

System	125
Waterproofing layer on the drain body	Adhesive flange (suitable for moisture barriers)
Sealing water height	50 mm

Dimensions

Vertical adjustment	|
Net weight	1.28 kg
Gross weight	1.86 kg
Diameter	348 mm
Height	215 mm
Packaging dimension: length	360 mm
Packaging dimension: width	360 mm
Packaging dimension: height	250 mm

Tank/drain body

Number of outlets	1
Material of drain body	Ecoguss resistant
Socket version	vertical